

The pracjourn class

KARL BERRY

ARTHUR OGAWA

WILL ROBERTSON

CORRESPONDENCE TO: PRACJOURN@TUG.ORG

2006/02/20 vo.4k

Abstract pracjourn is a class based on `article.cls`, to be used for typesetting articles in The PracTeX Journal, <http://tug.org/pracjourn>.

CONTENTS

1	Introduction	1	3	History	4
2	Usage	1	4	Implementation	4
2.1	Formatting	1	4.1	Base class and options	4
2.2	Author/article metadata	2	4.2	Metrics	5
2.3	Additional user commands	3	4.3	Package loading	5
2.4	TPJ internal commands	3	4.4	Amendments from article	6
2.5	Logos	3	4.5	TPJ additions	8

1 INTRODUCTION

The pracjourn L^AT_EX document class is to be used for articles written for the The PracTeX Journal, <http://tug.org/pracjourn>. The source for the document class resides at <http://tug.org/pracjourn/dtx>, and is also available at CTAN.

2 USAGE

Refer to the sample document, www.tug.org/pracjourn/dtx/pjsample.tex, for context. Issue a `\documentclass{pracjourn}` command at the beginning of your document as usual. No class options are necessary.

This document class automatically loads the packages `color`, `graphicx`, `hyperref`, and `textcomp`. These are all standard packages in every T_EX distribution.

2.1 Formatting

Page metrics are appropriate for printing on either A4 or letter size paper. The type size is 12/15.5 Palatino. Except in exceptional circumstances, please refrain from using typefaces other than those defined by this class.

Hyperlinks are inserted automatically in the relevant locations in a dark blue colour. If you wish to adjust this colour to suit your own colour requirements, simply redefine the `linkcolour`. E.g., to change it to dark red,

```
\definecolor{linkcolour}{rgb}{0.7,0.2,0.2}.
```

2.2 Author/article metadata

All author and article information must be defined before `\maketitle`, which should probably be the first thing after `\begin{document}`.

<code>\author</code>	The <code>\author</code> , <code>\title</code> , and <code>\abstract</code> commands are used to define those
<code>\title</code>	pieces of metadata about the article, and are mandatory. Note that the <code>\abstract</code>
<code>\abstract</code>	is a plain old command, <i>not</i> an environment.
<code>\noabstract</code>	Should you have a reason for not having an abstract, this may be signified by declaring <code>\noabstract</code> instead.
<code>\license</code>	It is optional to specify a copyright and/or license declaration, to be typeset in the footer of the first page, with the <code>\license</code> command. ¹
<code>\email</code>	Additional author information may be specified, to be typeset appropriately,
<code>\website</code>	with the following commands: <code>\email</code> , <code>\website</code> , and <code>\address</code> .
<code>\address</code>	If the <code>switcheml</code> package is installed somewhere that \TeX will find it, it is loaded for the purpose of obfuscating the typeset email address. This is done to prevent harvesting by spammers, but if the package cannot be found the email address will by typeset as a hyperlink.
<code>\hyperlinkemail</code>	Should you wish to typeset your email address as a hyperlink (that is, theoretically harvestable by spammers) despite having <code>switcheml</code> installed, you may simply include the command <code>\hyperlinkemail</code> anywhere before <code>\begin{document}</code> .

2.2.1 Adding more author/article information

As previously mentioned, this class provides the `\email`, `\website`, and `\address` macros for typesetting that information in the header block. These commands are defined in the source code of the class file with (something like) the following:²

```
\addinfo[\typesetemail]{Email}
\addinfo[\url]{Website}
\addinfo{Address}
```

Additional blocks may be added on a per-article basis in the same manner.

<code>\addinfo</code>	To be specific, the <code>\addinfo</code> command takes one mandatory argument, which is the title of the item to be added to the list, and one optional argument, which is used to define the formatting of the block.
	This command will then define the macro used to input the additional information by taking the lowercase of the title of the information and turning it into a \TeX macro. This creates the obvious limitation on the name of the information blocks that only single words may be used to describe any additional metadata. This should not cause concern in practice.
<code>\addinfospace</code>	If you wish to add some vertical space after the previous item in the front matter, the <code>\addinfospace{<height>}</code> command will insert some. This may be necessary after multi-line blocks, which require some breathing room.

1. The `\TPJcopyright` command, which used to provide this functionality is still provided for backwards compatibility.

2. `\typesetemail` is an internal command defined by either `\hyperlinkemail` or `\obfuscateemail`.

`\clearinfo` If you don't like the ordering of the information blocks or you wish to edit the formatting of the current setup, the `\clearinfo` command allows you to start fresh and redefine the address, email, and website information blocks however you may wish.

2.3 Additional user commands

`\dash` For 'smart' dashes in text. Thinly spaced from the text, it ignores surrounding spaces, and permits only succeeding line breaks.

use like this `\dash` for consistent dashes

produces 'use like this — for consistent dashes'.

`\note` For easier footnotes. This command ignores preceding space, so linebreaks before the footnote text in the source will not give the wrong spacing.

And here's an example.

`\note{Albeit a trivial one.}`

And continuing

produces 'And here's an example.³ And continuing'.

`itemise` For non-US writers, it is probably more natural to use `\begin{itemise}` over what \LaTeX provides by default.

`\ctanfile` These commands are used to refer to online locations and documentation within the Comprehensive \TeX Archive Network. Usage is as follows:

`\ctanloc`

`\ctanfile{macros/latex/contrib/titlesec/titlesec.pdf}`

`\ctanloc{macros/latex/contrib/titlesec/}`

It will print the input prefixed with 'CTAN:' and provide a hyperlink to the location.

2.4 TPJ internal commands

Two commands are to be used at the direction of the PracTeX production team: `\TPJrevision` and `\TPJissue`. These commands typeset information in the header of the first page relating to the revision number (or date) of the article and the issue number of the journal.

This document class creates a file `_rev.tex` in the current directory (if a `\TPJrevision` statement is present) and reads a file `_iss.tex`, if present. Please keep a separate directory for each article you develop for TPJ.

2.5 Logos

The following logos and abbreviations are defined for your convenience:

<code>\TeX:</code>	\TeX	<code>\BibTeX:</code>	BibTeX
<code>\LaTeX:</code>	\LaTeX	<code>\MF:</code>	METAFont
<code>\LaTeXe:</code>	$\text{\LaTeX}_{2\epsilon}$	<code>\MP:</code>	METAPOST

3. Albeit a trivial one.

<code>\ConTeXt:</code>	<code>ConT_EXt</code>	<code>\ExTeX:</code>	$\epsilon\chi$ T _E X
<code>\pdfTeX:</code>	<code>pdfT_EX</code>	<code>\PracTeX:</code>	PracT _E X
<code>\pdfLaTeX:</code>	<code>pdfL^AT_EX</code>	<code>\TPJ:</code>	The PracT _E X Journal
<code>\XeTeX:</code>	<code>X_ƎT_EX</code>	<code>\PS:</code>	PostScript

3 HISTORY

The first revision of this class was written by Karl Berry. KB: Gratefully based on the `dtxtut` skeleton.

Revised by Arthur Ogawa, 2004/01/03, to include new features, per Lance Carnes, as follows:

1. Define an `\articleID` macro which typesets the article identification in a block somewhere on the first page of the article, and which can be used to identify the article/revision date for reader comments. E.g. if this appears in the article source file:

```
\author{A.U. Thor}
\title{Pracjourn Sample}
\TPJissue{TPJ Vol 1 No 1, 2005-1-15}
\TPJrevision{2005-2-12}%
\TPJcopyright{\textcopyright\ 2005 TeX Users Group}
```

it will become a block of text typeset on the first page of the article. See e.g. [this example PDF](#).

2. Write the information from the argument of the `\articleID` macro into a file called `_id.tex`. Put this file in the same directory as the source file, and overwrite any previous files of the same name.
3. Define a `\TPJcopyright` macro which will print a copyright notice at the bottom of the first page. E.g. `\TPJcopyright{2005 TeX Users Group}` will produce “©2005 TeX Users Group” in the page footer of the title page.
4. The page measures should work with both Letter and A4 paper sizes.

Revised again by Will Robertson, mid-2005, to implement some extra things. This snow-balled into the current version, a description of which here would be redundant.

4 IMPLEMENTATION

The is fairly poorly documented, and the class has undergone a multitude of small changes over the TPJ issues 2005-4, 2006-1. It should now be fairly stable, and over time it's conceivable (but unlikely) that the descriptions herein will be improved.

4.1 Base class and options

Use L^AT_EX's article class, but at a bigger default type size.

KB: 12pt seems a little too big, 11pt seems a little too small. Implementing 11.5pt is not obvious.

If the document instance calls for options that conflict with the following choices, then the document wins. However our default option list is not the same as those of article.cls.

```
1 \let\ExecuteOptions@ltx\ExecuteOptions
2 \def\ExecuteOptions#1{%
3   \ExecuteOptions@ltx{letterpaper,12pt,oneside,onecolumn,final}%
4 }%
5 \LoadClassWithOptions{article}
6 \let\ExecuteOptions\ExecuteOptions@ltx
```

4.2 Metrics

Default leading (from classes.dtx) for 11pt is 13.6pt leading, for 12pt is 14.5pt. We want more—this factor gives us 12pt type on 15.5pt leading.

```
7 \linespread{1.069}
```

Change the text width to something that works for both A4 and Letter paper, as well as possible.

xx The vertical dimensions need to be changed as well, perhaps for a 9in text height, taking account of the headline and footline.

```
8 \setlength\textwidth{432pt}
9 \setlength\oddsidemargin{18pt}% xx depend on letter/a4
10 \setlength\evensidemargin{18pt}
```

4.3 Package loading

Palatino, including math (sc option for true small caps, not in TL 2003). Try for mathpazo; if not available use palatino.

Enable pdfT_EX's margin kerning, if available, but *not* font expansion, which increases the size and complexity of the resultant PDF. This side-effect may be deemed negligible in the future.

The textcomp package is loaded in order to provide a nice looking copyright logo, amongst other things.

```
11 \IfFileExists{mathpazo.sty}
12     {\RequirePackage[sc]{mathpazo}}
13     {\renewcommand\rmdefault{ppl}}
14 \IfFileExists{microtype.sty}{\RequirePackage[protrusion=true,expansion=false]{microtype}}{}
15 \RequirePackage{textcomp}
```

hyperref is used for creating live hyperlinks, as well as providing \url for type-setting URLs easily. All hyperlinks are coloured in a dark shade of blue.

```

16 \RequirePackage{color,hyperref,graphicx}
17 \definecolor{linkcolour}{rgb}{0,0.2,0.6}
18 \hypersetup{colorlinks,breaklinks,
19             linkcolor=linkcolour,citecolor=linkcolour,
20             filecolor=linkcolour, urlcolor=linkcolour}

```

If the switcheml package is installed in the author's system, use it to obfuscate their email address by default. Otherwise, just use a hyperlink. The commands to do this are defined in a later section.

An author may specify \hyperlinkemail explicitly should they not care to obfuscate their email address even with the switcheml package installed.

```

21 \IfFileExists{switcheml.sty}
22     {\RequirePackage{switcheml}
23      \AtBeginDocument{\@ifxundefined{typesetemail}{\obfuscateemail}{}}}
24     {\AtBeginDocument{\@ifxundefined{typesetemail}{\hyperlinkemail}{}}}

```

4.4 Amendments from article

`\maketitle` Printing the date of the last \TeX run in the title block does not seem warranted— if someone reprocesses the document with no changes, we wouldn't want the date to change.

xx use rcs.sty or something?
xx include bibtex id?

```

25 \renewcommand\maketitle{\par
26   \iftpj@noabstract\else
27     \@ifxundefined{tpj@info@Abstract}
28     {\ClassError{practjourn}
29      {Please specify an \string\abstract\space before \string\maketitle}
30      {It is a PracTeX Journal requirement to include an abstract. \MessageBreak
31                                             \MessageBreak
32      If you have exceptional reasons for not having one in this \MessageBreak
33      article, write \string\noabstract\space somewhere before \string\maketitle.}}{}
34   \fi
35   \begingroup
36     \renewcommand\thefootnote{\@fnsymbol\c@footnote}%
37     \def\@makefnmark{\rlap{\@textsuperscript{\normalfont\@thefnmark}}}%
38     \long\def\@makefntext##1{\parindent 1em\noindent
39       \hb@xt@1.8em{%
40         \hss\@textsuperscript{\normalfont\@thefnmark}}##1}%
41     \newpage
42     \global\@topnum\z@ % Prevents figures from going at top of page.
43     \@maketitle
44     \thispagestyle{titlepage}\@thanks
45   \endgroup
46   \setcounter{footnote}{0}%
47   \global\let\thanks\relax
48   \global\let\maketitle\relax
49   \global\let\@maketitle\relax

```

```

50 \global\let\title\relax
51 \global\let\author\relax
52 \global\let\date\relax
53 \global\let\and\relax
54 }%

```

\@maketitle

```

55 \def\@maketitle{%
56   \newpage
57   \null
58   \write@ID@aux\read@issue
59   \begin{flushleft}
60     \let\footnote\thanks
61     \begingroup\LARGE \@title \par\endgroup
62     \vspace{2ex}%
63     \begingroup\large \@author \par\endgroup
64   \end{flushleft}

```

This is where the extra author information is typeset. As various pieces of information are defined, they fill up the \tpj@optional@author@info macro, which is subsequently used here as per the definition of the author.

```

65 \tpj@optional@author@info
66 \iftpj@noabstract\else
67   \vspace{2ex}%
68   \tpj@info@container{Abstract}
69 \fi}

```

4.4.1 Formatting changes

\section	Remove bold from the all the section headings, just for something a little different.
\subsection	ent. This is verbatim from article.cls with a bunch of \bfseries's omitted.
\subsubsection	70 \renewcommand\section{\@startsection {section}{1}{\z@}%
\paragraph	71 {-3.5ex \@plus -1ex \@minus -.2ex}%
\subparagraph	72 {2.3ex \@plus .2ex}%
	73 {\normalfont\Large\raggedright}}
	74 \renewcommand\subsection{\@startsection{subsection}{2}{\z@}%
	75 {-3.25ex \@plus -1ex \@minus -.2ex}%
	76 {1.5ex \@plus .2ex}%
	77 {\normalfont\large\raggedright}}
	78 \renewcommand\subsubsection{\@startsection{subsubsection}{3}{\z@}%
	79 {-3.25ex \@plus -1ex \@minus -.2ex}%
	80 {1.5ex \@plus .2ex}%
	81 {\normalfont\normalsize\raggedright}}
	82 \renewcommand\paragraph{\@startsection{paragraph}{4}{\z@}%
	83 {3.25ex \@plus 1ex \@minus .2ex}%
	84 {-1em}%
	85 {\normalfont\normalsize\itshape}}
	86 \renewcommand\subparagraph{\@startsection{subparagraph}{5}{\parindent}%
	87 {3.25ex \@plus 1ex \@minus .2ex}%
	88 {-1em}%
	89 {\normalfont\normalsize\itshape}}

Lists

`itemize` Decrease the amount of vertical space between items in the list environments. To
`enumerate` do this, save the old environment macros under new names, and then change the
`description` ‘real’ environments to call the originals plus some space-adjusting parameters.

Note that description lists shouldn’t contain more than one paragraph.

```
90 \let\tpj@itemize\itemize
91 \let\tpj@enditemize\enditemize
92 \let\tpj@enum\enumerate
93 \let\tpj@endenum\endenumerate
94 \let\tpj@desc\description
95 \let\tpj@enddesc\enddescription
96 \renewenvironment{itemize}
97   {\tpj@itemize\parskip0pt}{\tpj@enditemize}
98 \renewenvironment{enumerate}
99   {\tpj@enum\parskip0pt}{\tpj@endenum}
100 \renewenvironment{description}
101   {\tpj@desc\parskip0pt\parindent1.8em}{\tpj@enddesc}
```

`itemise` Provide an environment with the correct spelling of ‘itemize’.

```
102 \let\itemise\itemize
103 \let\enditemise\enditemize
```

`\labelitemi(...)` Get rid of the nasty blob that is the `\textbullet`, and replace it with more unobtrusive dashes.

```
104 \renewcommand\labelitemi{\normalfont\bfseries\textendash}
105 \renewcommand\labelitemii{\normalfont\bfseries\textperiodcentered}
```

`\descriptionlabel` Change the description label to italics instead of bold.

```
106 \renewcommand*\descriptionlabel[1]{\hspace\labelsep
107   \normalfont\itshape #1}
```

Footnotes Here we change the footnote formatting a little bit from the default.

`\@makefnmark` Make the footnote number at the bottom of the page not a superscript (recommended by Bringham, if you’re curious—the superscript is there originally to get the number out of the way, but that’s no longer needed when you’re labelling the note with the number).

```
108 \renewcommand\@makefnmark[1]{%
109   \parindent 1.8em%
110   \noindent
111   \hb@xt@1.8em{\hbox{\strut\normalfont\small\@thefnmark.}\hss}#1}
```

4.5 TPJ additions

4.5.1 Boolean logic

`\@ifx@empty` The following three procedures implement part of the boolean logic facility, an
`\@ifx@undefined` expansion-only calculating engine.
`\@ifeof`


```

112 \def\@ifx@empty#1{% Implicit #2#3
113   \ifx#1\@empty
114     \expandafter\@firstoftwo
115   \else
116     \expandafter\@secondoftwo
117   \fi}%
118 \def\@ifx@undefined#1{% Implicit #2#3
119   \ifx#1\@undefined
120     \expandafter\@firstoftwo
121   \else
122     \expandafter\@secondoftwo
123   \fi}%
124 \def\@ifeof#1{% Implicit #2#3
125   \ifeof#1
126     \expandafter\@firstoftwo
127   \else
128     \expandafter\@secondoftwo
129   \fi}%
130 \def\boolean@true#1{\let#1\@firstoftwo}%
131 \def\boolean@false#1{\let#1\@secondoftwo}%

```

4.5.2 Titlepage pagestyle

`\ps@titlepage` The `\ps@titlepage` procedure effects a page style called `titlepage`, which applies only to the title page. The `\titlepage@head` procedure sets type in the page header, `\titlepage@foot` in the page footer.

```

132 \def\ps@titlepage{%
133   \def\@oddhead{\titlepage@head\hfil}%
134   \let\@evenhead\@oddhead
135   \def\@oddfoot{\hfil\titlepage@foot}%
136   \let\@evenfoot\@oddfoot}%

```

`\titlepage@head` This is the text block before the article title. Changes depending on the production stage.

```

137 \def\titlepage@head{\footnotesize
138   \parbox{\linewidth}{%
139     \@ifx@empty\@TPJissue{For submission to \TPJ}{\@TPJissue}\par
140     \@ifx@empty\@TPJissue
141       {\@ifx@empty\@TPJrevision{Draft of \today}{Article revision \@TPJrevision}}%
142       {\@ifx@empty\@TPJrevision
143         {\ClassError{pracjourn}
144           {\string\TPJrevision\space must be defined if
145             \string\TPJissue\space is also}
146           {It is a requirement for PracTeX Journal articles to contain\MessageBreak
147             revision information for version tracking. Please input this\MessageBreak
148             information, or omit \protect\TPJissue.}}
149           {Article revision \@TPJrevision}}}%

```

`\titlepage@foot` To typeset the optional copyright declaration by the author.

```

150 \def\titlepage@foot{%
151   \vtop{\raggedleft\footnotesize\@TPJcopyright}}%

```

```

152 % Better float parameters: (from the TeX FAQ)
153 \renewcommand{\topfraction}{.85}
154 \renewcommand{\bottomfraction}{.7}
155 \renewcommand{\textfraction}{.15}
156 \renewcommand{\floatpagefraction}{.66}
157 \renewcommand{\dbltopfraction}{.66}
158 \renewcommand{\dblfloatpagefraction}{.66}
159 \setcounter{topnumber}{9}
160 \setcounter{bottomnumber}{9}
161 \setcounter{totalnumber}{20}
162 \setcounter{dbltopnumber}{9}

```

4.5.3 Additional author/article information

`\addinfo` This command defines a new block of information to be typeset in the title block of the document. For every new item, a new `\tpj@info@container` is appended to `\tpj@optional@author@info`, which is called in `\@maketitle`.

```

163 \newcommand\addinfo[2][]{%
164   \tpj@define@info@block[#1]{#2}%
165   \g@addto@macro\tpj@optional@author@info{\tpj@info@container[#1]{#2}}}

```

`\addinfospace` Adds some space after the previous item in the frontmatter.

```

166 \newcommand\addinfospace[1]{\g@addto@macro\tpj@optional@author@info{\vspace{#1}}}

```

`\tpj@define@info@block` This macro actually does the work of `\addinfo`. It takes the name of a piece of info to be typeset in the title block of the article. The name of the info is lowercased to create a control sequence for the user to input this data. E.g., `\addinfoAbstract` will create a control sequence `\abstract` which saves its argument inside `\tpj@info@Abstract`.

All commands are defined `\long` so that paragraphs are allowed. This is much easier than `\begin{abstract}... \end{abstract}` contortions (cf. `ltugboat.cls`).

```

167 \newcommand\tpj@define@info@block[2][]{%
168   \lowercase{\expandafter\long\expandafter\def\csname#2\endcsname}%
169   ##1{\expandafter\def\csname tpj@info@#2\endcsname{##1}}}

```

`\clearinfo` If the `\tpj@optional@author@info` macro needs to be cleared for some reason,⁴ the `\clearinfo` command will come quite in handy. This command is also used to initialise the macro in question.

```

170 \newcommand\clearinfo{\let\tpj@optional@author@info\@empty}
171 \clearinfo

```

Optional fields These are the default information blocks. `\typesetemail` is defined by one of either `\hyperlinkemail` or `\obfuscateemail`.

```

172 \addinfo[\typesetemail]{Email}
173 \addinfo[\url]{Website}
174 \addinfo[\linespread{0.9}\selectfont]{Address}

```

4. The only reason I can think of to do this is to re-arrange the order of the items in the title block of the article.

Abstract We bypass `\addinfo` so that the abstract info block is not added to the `\tpj@optional@author@info` macro.

The abstract block itself is called directly in `\@maketitle`.

```
175 \tpj@define@info@block{Abstract}
```

`\noabstract` However, the abstract may indeed be suppressed if that is the author's wish.

```
176 \newif\iftpj@noabstract
```

```
177 \newcommand\noabstract{\tpj@noabstracttrue}
```

`\endabstract` If an abstract environment is used, give an error. Maybe I should just support the environment, instead.

```
178 \def\endabstract{%
```

```
179   \ClassError{pracjourn}
```

```
180   {Please input the abstract with \string\abstract{...}, before \string\begin{document}}
```

```
181   {Instead of the \string\begin{abstract}...\string\end{abstract} \MessageBreak
```

```
182   environment, use \string\abstract{...}. Paragraphs are allowed!\MessageBreak
```

```
183                                     \MessageBreak
```

```
184   Because the abstract is typeset with the title block, \MessageBreak
```

```
185   it must be input before the \string\begin{document}\space command.}}
```

`\TPJissue` The three user-level commands `\TPJissue`, `\TPJrevision`, and `\TPJcopyright` specify the issue, the revision, and the copyright information of the document.

`\TPJrevision` Since these commands are like `\author` and `\title`, one might wish to disable them upon executing the `\titlepage` procedure. But we do not.

`\TPJcopyright` If the document has a `\TPJrevision` statement, the title page header contains words to that effect, otherwise it bears the current date.

If the document lacks a `\TPJcopyright` statement, the title page footer contains nothing.

```
186 \newcommand{\TPJissue}[2]{\gdef\@TPJissue{\TPJ, #1, No.\, #2}}%
```

```
187 \newcommand{\TPJrevision}[3]{\gdef\@TPJrevision{#1/#2/#3}}%
```

```
188 \newcommand{\TPJcopyright}[1]{\gdef\@TPJcopyright{#1}}%
```

```
189 \let\@TPJissue\@empty
```

```
190 \let\@TPJrevision\@empty
```

```
191 \let\@TPJcopyright\@empty
```

`\license` For consistency with the other user commands of this class, `\license` is defined as an alias of `\TPJcopyright`.

```
192 \let\license\TPJcopyright
```

`\tpj@info@container` This is the macro that typesets the optional author info for fields defined as above. It splits it all up in minipages, in a smaller font and with more compressed leading than the main document text.⁵ It takes the name of the info as a mandatory argument, which is used to typeset the info label as well as retrieve the actual data from the `\tpj@info@#1` macro (see `\addinfo`).

An optional argument is used as a hook to typeset the info data in the equivalent form `#1{#2}`.

5. L^AT_EX's `\@hangfrom` (or whatever it is) could well have been much easier.

For example, to typeset the info defined by the author in the `\abstract` (recall, this is set up due to a corresponding `\addinfo{Abstract}`—see above), input `\tpj@info@container{Abstract}`. To typeset it, say, in italics, it would be possible to write `\tpj@info@container[\textit]{Abstract}`.

```
193 \newcommand\tpj@info@container[2] [] {%
```

After `\maketitle`, redefine the info command to return an error.

```
194 \lowercase{\expandafter\gdef\csname#2\endcsname}%
195 {\ClassError{prajourn}{#2 must be defined BEFORE \string\maketitle}{}}
```

Now, we typeset the info block, but only if the info has actually been specified by the author.

```
196 \expandafter\ifx\csname tpj@info@#2\endcsname\relax\else
197 \noindent\null\hfill\small
```

On the left, right-aligned sans serif item label, e.g., ‘Abstract’:

```
198 \begin{minipage}[t]{0.1\textwidth}
199 \noindent\hfill\sffamily#2
200 \end{minipage}\hfill
```

On the right, the content, defined by, e.g., `\abstract`:

```
201 \begin{minipage}[t]{0.85\textwidth}
202 \linespread{1.0}\selectfont
203 \setlength\parindent{1.5em}%
204 \noindent\ignorespaces
205 \expandafter#1\expandafter{\csname tpj@info@#2\endcsname}
206 \end{minipage}\par
207 \fi}
```

4.5.4 Email & hyperlink macros

`\typesetemail` We define the macro `\typesetemail` to be used for self-explanatory purposes. The class contains methods to define it in one of two ways.

`\hyperlinkemail` The `\hyperlinkemail` command defines `\typesetemail` to use the `hyperref` package’s facilities to create a hyperlink email address in the output document.

`\obfuscateemail` The `\obfuscateemail` command defines `\typesetemail` to use the `switcheml` package’s facilities to create a machine-obfuscated email address in the output document.⁶

```
208 \newcommand\obfuscateemail{%
209 \def\typesetemail##1{\ttfamily\switchemail{##1}}
210 \newcommand\hyperlinkemail{%
211 \def\typesetemail##1{\ttfamily\tpj@compose@mailto{##1}{Re: PracTeX Journal article}{##1}}}
```

`\tpj@compose@mailto` This macro takes three arguments to typeset a mailto email hyperlink. The #1 takes the email address, #2 takes the default subject of the email, and #3 is the text to appear in the output as the hyperlink.

6. The `switcheml` package defines, among a couple of other things, a macro for typesetting email addresses that obfuscates their representation in the PDF file, ensuring protection against harvesting email addresses from web-public PDF documents.

All spaces in the hyperlink source are converted to %20 to accommodate Mac OS X's PDF reader; this isn't necessary for Adobe Reader. Oh well.

```
212 \newcommand\tpj@compose@mailto[3]{%
213   \edef\@tempa{mailto:#1?subject=#2 }%
214   \edef\@tempb{\expandafter\html@spaces\@tempa\@empty}%
215   \href{\@tempb}{#3}}
```

`\html@spaces` This macro takes a string and (hopefully) converts all spaces (or is it all whitespaces?) to “%20”, creating a string that can be used for encoding the subject of the email comments hyperlink in `\titlepage@head`. Using `\catcode`, we remove the comment ability of the % character, making it a normal letter. (This code was heavily influenced by the L^AT_EX kernel's `\zap@space` command.)

```
216 \catcode'\%=11
217 \def\html@spaces#1 #2{#1%20\ifx#2\@empty\else\expandafter\html@spaces\fi#2}
218 \catcode'\%=14
```

4.5.5 User commands

```
\note Fairly straightforward.
\dash 219 \newcommand\note[1]{\unskip\footnote{#1}}
\ctanfile 220 \DeclareRobustCommand\dash{%
\ctanloc 221   \unskip\nobreak\thinspace\textemdash\thinspace\ignorespaces}
222 \pdfstringdefDisableCommands{\renewcommand{\dash}{ - }}
223 \newcommand\ctanfile[1]{%
224   \href{http://www.ctan.org/get?fn=#1}
225     {\path{CTAN:#1}}}
226 \newcommand\ctanloc[1]{%
227   \href{http://www.ctan.org/tex-archive/#1}
228     {\path{CTAN:#1}}}
```

4.5.6 Logos

The `texnames` and `mflogo` packages have been incorporated into the class in order to remove the dependence on external packages and to tune the logos for Palatino. First, here are the relevant parts⁷ of `texnames.sty`, v1.10, tuned for Palatino and adapted to use `\textsc` where appropriate:

```
229 \DeclareRobustCommand\TeX{T\kern-.15em\lower.5ex\hbox{E}\kern-.07em X\spacefactor1000\relax}
230 \DeclareRobustCommand\LaTeX{L\kern-.32em\raise.37ex\hbox{\scalebox{0.76}{A}}\kern-.15em\TeX}
231 \DeclareRobustCommand\LaTeXe{\LaTeX2$_{\textstyle\varepsilon}$}
232 \DeclareRobustCommand\BibTeX{B{\textsc i}\kern-.025em\textsc b}\kern-.08em\TeX}
```

And now `mflogo.sty`, unchanged in its entirety:

```
233 \DeclareRobustCommand\logofamily{%
234   \not@math@alphabet\logofamily\relax
235   \fontencoding{U}\fontfamily{logo}\selectfont}
236 \DeclareTextFontCommand{\textlogo}{\logofamily}
237 \DeclareRobustCommand\MF{\textlogo{META}\@dischyph\textlogo{FONT}\@}
238 \DeclareRobustCommand\MP{\textlogo{META}\@dischyph\textlogo{POST}\@}
```

7. No-one still refers to AMSTeX and SLiTeX and so on, right?

Now some new definitions. Despite the fact that it makes no difference with the main font used for this class, I define `\pdfTeX` with some italic correction to set a good precedent. Compare Computer Modern with and without: `pdfTeX` vs. `pdfTeX`; I find the former more attractive because the ascender of the ‘f’ doesn’t collide.

```

239 \DeclareRobustCommand\ConTeXt{\kern-.03em on\-\kern-.10em\TeX\kern-0.04em t}%
240 \DeclareRobustCommand\pdfTeX{\pdf\/\TeX}
241 \DeclareRobustCommand\pdfLaTeX{\pdf\/\LaTeX}
242 \DeclareRobustCommand\PS{PostScript}
243 \DeclareRobustCommand\PracTeX{\Prac\kern-0.07em\TeX}
244 \DeclareRobustCommand\TPJ{The \PracTeX\ Journal}
245 \DeclareRobustCommand\XeTeX{%
246     X\lower.5ex\hbox{\kern-.07em\reflectbox{E}}}%
247     \kern-.15em\TeX}
248 \DeclareRobustCommand\ExTeX{\textrm{\relax
249     \ensuremath{\textstyle\varepsilon_{\kern-0.15em\mathcal{X}}}}\relax
250     \kern-.15em\TeX}}

```

4.5.7 Version tracking

`\write@ID@aux` Establish an auxiliary file, `_id.tex`, for TPJ tracking information.

```

251 \def\write@ID@aux{%
252   \ifx@empty\@TPJrevision{}\{%
253     \begingroup
254       \let\thanks\@gobble
255       \immediate\openout\ID@aux _rev.tex
256 %   \immediate\write\ID@aux{\@percentchar\space
257 %     This file generated by the pracjourn document class}%
258       \immediate\write\ID@aux{\@TPJrevision}%
259       \immediate\closeout\ID@aux
260     \endgroup
261   }%
262 }%
263 \newwrite\ID@aux

```

`\read@iss@aux`

```

264 \def\read@issue{%
265   \openin\@inputcheck _iss.tex
266   \ifeof\@inputcheck{}
267   {\ifx\@TPJissue\@empty\else
268     \typeout{-----^^J
269               pracjourn: \protect\TPJissue\space info overwritten due to _iss.tex file^^J
270             -----}
271     \fi
272     \read\@inputcheck to\@TPJissue
273     \closein\@inputcheck
274     \expandafter\parse@iss\@TPJissue\@nil}}

```

`\parse@iss`

```

275 \def\parse@iss TPJ #1 No #2, #3-#4-#5\@nil{%
276   \@tempcnta#2\relax
277   \protected@xdef\@TPJissue{\TPJ, #1, No.\, \the\@tempcnta}}

```

4.5.8 Miscellaneous

`\set@pdfpage` The PDF_TE_X parameters `\pdfpagewidth` and `\pdfpageheight` determine the CropBox/BleedBox/TrimBox/ArtBox. The procedure `\setpdfpage` sets them to the values of the L^AT_EX `\paperwidth` and `\paperheight`. If PDF_TE_X is not the engine, nothing is done.

We arrange for the procedure to be executed at Begin Document time.

```

278 \def\set@pdfpage{%
279   \@ifx@undefined\pdfoutput{}\{%
280     \pdfpagewidth =\paperwidth
281     \pdfpageheight=\paperheight
282     \relax}}
283 \AtBeginDocument{\set@pdfpage}

```

CHANGE HISTORY

vo.0	General: KB: Initial version 1	vo.4b	\html@spaces: WR: Implemented to overcome the mailto problems in Mac OS X's PDF reader. 13
vo.2	General: KB: Palatino, no date printing 1	\maketitle: WR: added check for an abstract 6	WR: removed some twocolumn conditional code. 6
vo.3	General: AO: Add \TPJissue, \TPJrevision, \TPJcopyright . 1	\titlepage@head: WR: Added hyperref link to email article comments for both reviewers and readers. 9	WR: More conditional text. . . . 9
	AO: Override the default option list of article.cls 5	\tpj@compose@mailto: WR: Implemented; creates a workable mailto hyperlink. 13	
	AO: rewrite using \IfFileExists idiom. 5		
	AO: Rewrite using L ^A T _E X _{2ϵ} idioms 1	vo.4c	\titlepage@head: WR: Added error check for \TPJrevision defined without \TPJissue. 9
	\maketitle: AO: \thispagestyle{titlepage}. Do not empty out \@author, \@title, etc. 6	vo.4d	\addinfo: WR: Name change to user-space. 10
	AO: reproduce entire definition from article.cls, with modifications. 6	\clearinfo: WR: Implemented to allow for re-definition of standard information blocks. 10	
	\ps@titlepage: AO: add page header and footer to title page . 9	\license: WR: name change from \TPJcopyright for consistency with other commands. 11	
	\read@iss@aux: AO: read the "issue" file. 15	\noabstract: WR: Implemented to turn off the abstract. 11	
	\set@pdfpage: AO: add commands setting pdftex's page metrics from LaTeX's 15	\titlepage@foot: WR: Removed \copyright from the copyright notice and put the whole thing in a lowered \vbox to allow multi-line declarations. 10	
	\TPJcopyright: AO: add commands specifying issue, revision, copyright. 11	\titlepage@head: WR: Make the header \small. 9	
	\write@ID@aux: AO: add ID file . 14	\tpj@info@container: WR: Warn if a title block command is used after \maketitle. 12	
vo.3a	General: AO: changes to \TPJissue, \TPJrevision, \TPJcopyright . 1	vo.4e	General: WR: requires the textcomp package. 5
vo.3b	General: AO: change \evensidemargin 1	\titlepage@head: WR: Removed email comments links. 9	
vo.4a	\@maketitle: WR: various changes to accommodate extras. 7		
	General: WR: Incorporated code from texnames and mflogo. . . . 13		
	\tpj@define@info@block: WR: Implemented for new \@maketitle. 10		
	\tpj@info@container: WR: Implemented for new \@maketitle. . 12		

vo.4f		section headings.	7
	\@makefnstext: WR: Removed the footnote superscript		8
vo.4g		vo.4j	
	\@makefnstext: WR: Added a period after the footnote number	General: Added \XeTeX logo.	14
	General: WR: use microtype, if available	Implemented.	3
	description: Space removed between list items.		5
	\labelitemi(...): Itemise bullets changed.	vo.4k	
vo.4i		General: Added \ExTeX logo.	14
	\read@iss@aux: WR: _iss.tex behaviour finally sorted out.	\parse@iss: WR: Implemented for better article headers.	15
	\section: Added \raggedright to	\titlepage@foot: WR: Made smaller.	10
		\titlepage@head: WR: Simplified & made smaller.	9
		\TPJissue: WR: More user-friendly.	11
		\TPJrevision: WR: More user-friendly.	11

INDEX

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols		
$\%$	216, 218	$\@startsection$
$\,$	186, 277	.. 70, 74, 78, 82, 86
$\-$	239	$\@tempa$
$\/$	240, 241	213, 214
$\@$	237, 238	$\@tempb$
$\@TPJcopyright$	151, 188, 191	214, 215
$\@TPJissue$	139,	$\@tempcnta$
140, 186, 189,		276, 277
267, 272, 274, 277		$\@textsuperscript$ 37, 40
$\@TPJrevision$	141, 142, 149,	$\@thanks$
187, 190, 252, 258		44
$\@author$	63	$\@thefnmark$. 37, 40, 111
$\@dischyph$	237, 238	$\@title$
$\@empty$ 113, 170, 189–		61
191, 214, 217, 267		$\@topnum$
$\@evenfoot$	136	42
$\@evenhead$	134	$\@undefined$
$\@firstoftwo$	114, 120, 126, 130	119
$\@fnsymbol$	36	$_$
$\@gobble$	254	244
$\@ifeof$	<u>112</u> , 266	
$\@ifx@empty$	<u>112</u> , 139–142, 252	
$\@ifx@undefined$	23, 24, 27, <u>112</u> , 279	
$\@inputcheck$	265, 266, 272, 273	
$\@makefnmark$	37	
$\@makefntext$	38, <u>108</u>	
$\@maketitle$	43, 49, <u>55</u>	
$\@minus$. 71, 75, 79, 83, 87		
$\@nil$	274, 275	
$\@oddfoot$	135, 136	
$\@oddhead$	133, 134	
$\@percentchar$	256	
$\@plus$	71, 72,	
75, 76, 79, 80, 83, 87		
$\@secondoftwo$	116, 122, 128, 131	
		A
		\abstract
		29, 180, 182
		\addinfo
		<u>163</u> , 172–174
		\addinfospace
		<u>166</u>
		\and
		53
		\AtBeginDocument
		23, 24, 283
		\author
		51
		B
		\begin
		59, 180,
		181, 185, 198, 201
		\begingroup 35, 61, 63, 253
		\bfseries
		104, 105
		\BibTeX
		232
		$\boolean@false$
		131
		$\boolean@true$
		130
		\bottomfraction
		154
		C
		$\c@footnote$
		36
		\catcode
		216, 218
		\ClassError
		28, 143, 179, 195
		\clearinfo
		<u>170</u>
		\closein
		273
		\closeout
		259
		\ConTeXt
		239
		\csname
		168,
		169, 194, 196, 205
		\ctanfile
		<u>219</u>
		\ctanloc
		<u>219</u>
		D
		\dash
		<u>219</u>
		\date
		52
		\dblfloatpagefraction
		158
		\dbltopfraction
		157
		\DeclareRobustCommand
		220, 229–
		233, 237–245, 248
		\DeclareTextFontCommand
		236
		\def
		2, 37,
		38, 55, 112, 118,
		124, 130–133,
		135, 137, 150,
		168, 169, 178,
		209, 211, 217,
		251, 264, 275, 278
		\definecolor
		17
		\description
		94
		description (environ-
		ment)
		<u>90</u>
		\descriptionlabel
		<u>106</u>
		E
		\edef
		213, 214
		\else . 26, 66, 115, 121,
		127, 196, 217, 267
		\end
		64, 181, 200, 206
		\endabstract
		<u>178</u>
		\endcsname
		168,
		169, 194, 196, 205
		\enddescription
		95
		\endenumerate
		93
		\endgroup 45, 61, 63, 260
		\enditemize
		103
		\enditemize
		91, 103
		\ensurermath
		249
		\enumerate
		92
		enumerate (environ-
		ment)
		<u>90</u>

environments:	\immediate	\newif 176
description <u>90</u>	. 255, 256, 258, 259	\newpage 41, 56
enumerate <u>90</u>	\itemise 102	\newwrite 263
itemise <u>102</u>	itemise (environment) <u>102</u>	\noabstract 33, <u>176</u>
itemize <u>90</u>	\itemize 90, 102	\nobreak 221
\evensidemargin 10	itemize (environment) <u>90</u>	\noindent 38,
\ExecuteOptions . . . 1, 2, 6	\itshape 85, 89, 107	110, 197, 199, 204
\ExecuteOptions@ltx		\normalfont 37,
. 1, 3, 6	K	40, 73, 77, 81, 85,
\expandafter . . . 114,	\kern 229, 230,	89, 104, 105, 107, 111
116, 120, 122,	232, 239, 243,	\normalsize . . 81, 85, 89
126, 128, 168,	246, 247, 249, 250	\not@math@alphabet 234
169, 194, 196,		\note <u>219</u>
205, 214, 217, 274	L	\null 57, 197
\ExTeX 248	\labelitemi 104	
	\labelitemi(...) . . <u>104</u>	O
	\labelitemii 105	\obfuscateemail . 23, <u>208</u>
F	\labelsep 106	\oddsidemargin 9
\fi . . 34, 69, 117, 123,	\LARGE 61	\openin 265
129, 207, 217, 271	\Large 73	\openout 255
\floatpagefraction 156	\large 63, 77	
\fontencoding 235	\LaTeX 230, 231, 241	P
\fontfamily 235	\LaTeXe 231	\paperheight 281
\footnote 60, 219	\let 1, 6, 47–53, 60, 90–	\paperwidth 280
\footnotesize . . 137, 151	95, 102, 103, 130,	\par . . 25, 61, 63, 139, 206
	131, 134, 136,	\paragraph <u>70</u>
G	170, 189–192, 254	\parbox 138
\g@addto@macro . 165, 166	\license <u>192</u>	\parindent
\gdef 186–188, 194	\linespread . . 7, 174, 202	38, 86, 101, 109, 203
\global 42, 47–53	\linewidth 138	\parse@iss 274, <u>275</u>
	\LoadClassWithOptions	\parskip 97, 99, 101
H 5	\path 225, 228
\hb@xt@ 39, 111	\logofamily 233, 234, 236	\pdfLaTeX 241
\hbox . . 111, 229, 230, 246	\long 38, 168	\pdfoutput 279
\hfil 133, 135	\lower 229, 246	\pdfpageheight 281
\hfill 197, 199, 200	\lowercase 168, 194	\pdfpagewidth 280
\href 215, 224, 227		\pdfstringdefDisableCommands
\hspace 106	M 222
\hss 40, 111	\maketitle <u>25</u> , 195	\pdfTeX 240
\html@spaces . . . 214, <u>216</u>	\mathcal 249	\PracTeX 243, 244
\hyperlinkemail . 24, <u>208</u>	\MessageBreak . . 30–	\protect 148, 269
\hypersetup 18	32, 146, 147, 181–184	\protected@xdef . . . 277
	\MF 237	\PS 242
I	\MP 238	\ps@titlepage <u>132</u>
\ID@aux 255,		
256, 258, 259, 263	N	R
\ifeof 125	\newcommand . . . 163,	\raggedleft 151
\IfFileExists . . 11, 14, 21	166, 167, 170,	\raggedright . . 73, 77, 81
\iftpj@noabstract .	177, 186–188,	\raise 230
. 26, 66, 176	193, 208, 210,	\read 272
\ifx 113, 119, 196, 217, 267	212, 219, 223, 226	\read@iss@aux <u>264</u>
\ignorespaces . . 204, 221		

<code>\read@issue</code> 58, 264	<code>\switchemail</code> 209	<code>\tpj@info@Abstract</code> . 27
<code>\reflectbox</code> 246		<code>\tpj@info@container</code>
<code>\relax</code> 47–	T 68, 165, <u>193</u>
53, 196, 229, 234,	<code>\TeX</code> 229, 230, 232, 239,	<code>\tpj@itemize</code> 90, 97
248, 249, 276, 282	240, 243, 247, 250	<code>\tpj@noabstracttrue</code> 177
<code>\renewcommand</code> . . . 13,	<code>\textemdash</code> 221	<code>\tpj@optional@author@info</code>
25, 36, 70, 74, 78,	<code>\textendash</code> 104	. . . 65, 165, 166, 170
82, 86, 104–106,	<code>\textfraction</code> 155	<code>\TPJcopyright</code> . . <u>186</u> , 192
108, 153–158, 222	<code>\textlogo</code> 236–238	<code>\TPJissue</code>
<code>\renewenvironment</code> .	<code>\textperiodcentered</code> 105	. . 145, 148, <u>186</u> , 269
. 96, 98, 100	<code>\textrm</code> 248	<code>\TPJrevision</code> . . . 144, <u>186</u>
<code>\RequirePackage</code> . .	<code>\textsc</code> 232	<code>\ttfamily</code> 209, 211
. 12, 14–16, 22	<code>\textstyle</code> 231, 249	<code>\typeout</code> 268
<code>\rlap</code> 37	<code>\textwidth</code> . . . 8, 198, 201	<code>\typesetemail</code>
<code>\rmdefault</code> 13	<code>\thanks</code> 47, 60, 254	. . . 23, 24, 172, <u>208</u>
S	<code>\the</code> 277	
<code>\scalebox</code> 230	<code>\thefootnote</code> 36	U
<code>\section</code> <u>70</u>	<code>\thinspace</code> 221	<code>\unskip</code> 219, 221
<code>\selectfont</code> 174, 202, 235	<code>\thispagestyle</code> 44	<code>\url</code> 173
<code>\set@pdfpage</code> <u>278</u>	<code>\title</code> 50	V
<code>\setcounter</code> 46, 159–162	<code>\titlepage@foot</code> 135, <u>150</u>	<code>\varepsilon</code> . . . 231, 249
<code>\setlength</code> . . . 8–10, 203	<code>\titlepage@head</code> 133, <u>137</u>	<code>\vspace</code> 62, 67, 166
<code>\sffamily</code> 199	<code>\today</code> 141	<code>\vtop</code> 151
<code>\small</code> 111, 197	<code>\topfraction</code> 153	
<code>\space</code> . . . 29, 33, 144,	<code>\TPJ</code> . . . 139, 186, 244, 277	W
145, 185, 256, 269	<code>\tpj@compose@mailto</code>	<code>\write</code> 256, 258
<code>\spacefactor</code> 229 211, <u>212</u>	<code>\write@ID@aux</code> . . . 58, <u>251</u>
<code>\string</code> 29, 33, 144, 145,	<code>\tpj@define@info@block</code>	
180–182, 185, 195 164, <u>167</u> , 175	X
<code>\strut</code> 111	<code>\tpj@desc</code> 94, 101	<code>\XeTeX</code> 245
<code>\subparagraph</code> <u>70</u>	<code>\tpj@enddesc</code> 95, 101	
<code>\subsection</code> <u>70</u>	<code>\tpj@endenum</code> 93, 99	Z
<code>\subsubsection</code> <u>70</u>	<code>\tpj@enditemize</code> . . . 91, 97	<code>\z@</code> 42, 70, 74, 78, 82
	<code>\tpj@enum</code> 92, 99	